

SP900

Thermal Receipt Printer



- Simple & Fashionable Appearance
- Compatible with 2-inch / 3-inch paper roll
- Easy paper loading with front paper output structure
- Support auto-retreat function when cutter jam
- Support Paper Saving Mode
- Provide multi-system driver program



Specification

Items		Parameter
Printing	Printing Method	Thermal printing
	Resolution	203dpi (8dots/mm)
	Printing Width	72mm(default)/48mm
	Printing Speed	Max.260mm/s
	Emulation	ESC/POS
Media	Types	Thermal continuous paper
	Width	80mm
	Paper Container Capacity	Max.83mm
	Paper Output Direction	Top output
Communication Interface	Standard Optional	USB Type-B, Cash drawer, Ethernet WiFi, BT
Beeper	Type	Built-in beeper
Sensors	Standard Optional	Over-temperature, paper end, cover opening and cutter jam sensors Black mark sensor
Memory	RAM	4MB
	Flash	4MB
Electrical Characteristic	Input	AC100~240V, 50/60Hz
	Output	24VDC 2.5A
Software	Driver	Windows 7/8/10, Windows Server 2008/2012/2016 Linux, Javapos, OPOS, MacOS
	Utility Tool	Windows 7/8/10, Windows Server 2008/2012/2016
Reliability	Thermal Print Head	150km
	Cutter Life Span	2million
	Drop Height	1.0m
Environmental Specifications	Operation	0~40°C, relative humidity 20~85%, non-condensing
	Storage/Transportation	-20~70°C, relative humidity 5~95%, non-condensing
Certification		CCC, CE, FCC
Size (mm)		130*119.3*165.4
Weight (kg)		1.24

Application



Xiamen Hanin Electronic Technology Co.,Ltd.

ADD: 5F, 10# Building, Gaoqi South 12 Road, Aide Industrial Park, Huli District, Xiamen, P.R China

TEL: +86-(0)592-5932525 FAX: +86-(0)592-5885992

WEB: www.idprt.com EMAIL: info@idprt.com



iDPRT Official Website